

SOLIDEAL AIR 561

BY CAMSO



GROUND SUPPORT
EQUIPMENT



PERFECT SOLUTION FOR GROUND SUPPORT EQUIPMENT

Especially designed for ground support equipment, this tyre delivers great life on high temperature apron surfaces while ensuring low rolling resistance and increased traction.

camso.co

PERFORMANCE

TYRE LIFE



PUNCTURE RESISTANCE



STABILITY



FORMERLY
CAMOPLAST
SOLIDEAL

GROUND SUPPORT EQUIPMENT

SOLIDEAL AIR 561

BY CAMSO

TYRE SIZE	PR	TUBE* & VALVE**	FLAP	RIM SIZE ⁽¹⁾		ACTUAL TYRE DIMENSIONS				INFLATION PRESSURE (bar)	LOAD INDEX & SPEED SYMBOL	LOAD CAPACITY ⁽²⁾ Counterbalanced lift trucks (kg)				
				Recommended	Alternative	Overall diameter (mm)	Section width (mm)	Original tread depth (mm)	Static loaded radius (mm)			Up to 25 km/h		Up to 35 km/h		
												Load wheel	Steering wheel	Load wheel	Steering wheel	
6.00 - 9	10	JS2	125 - 9	4.00	-	540	163	12	-	10.00	111	A5	1415	1090	1365	1015
6.50 - 10	10	JS2	140 - 10	5.00	-	597	178	13	-	8.50	111	A5	1415	1090	1365	1015
7.00 - 12	14	TR75A	135 - 12	5.00	-	671	188	15	-	10.00	125	A5	2145	1650	2065	1535
7.00 - 15	14	TR75A	180 - 15	5.50	-	757	194	17	-	8.50	118	A5	1715	1320	1650	1230
8.00 - 16.5	10	TBLS	-	6.00	-	736	220	16	-	9.00	131	A5	2535	1950	2440	1815
8.75 - 16.5	10	TBLS	-	6.00	-	757	224	18	-	7.75	122	A5	1950	1500	1875	1395
9.50 - 16.5	10	TBLS	-	6.50	7.00	797	253	18	-	10.00	128	A5	2340	1800	2250	1675

DISTINCTIVE RIB PATTERN DESIGN

- Reduces rolling resistance, vibrations and prevents snaking

UNIQUE LUGS WITH SIPES DESIGN

- Increases traction on low grip conditions



DEEP TREAD LUGS WITH HIGH PERFORMANCE COMPOUND

- Increases tyre life

ENERGY-EFFICIENT RUBBER COMPOUND

- Helps reduce wear on heated airport apron surfaces

Remarks

(1) Consult tyre and wheel manufacturer for confirmation of the suitability of the tyre/rim combination particularly with regard to rim profile and wheel strength.

(2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted. Loads apply to cyclic service applications. Cyclic service means applications where tyre are not used continuously at the load indicated by its Load Index and Speed Symbol. It does not refer to the length of time a vehicle is in use, but rather that there is a variation in load and/or speed.

* Tube size is identical to tyre size

** Table shows standard valves. Other valves on request.

NHS – Not for Highway Service: Tyres primarily designed for use outside of public roads, but suitable for temporary/incidental use on public roads.

All tyres come with tube and flap.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tyre availability in your region.

AUTHORIZED DISTRIBUTOR:



Camso is the best of Camoplast and Solideal.
To keep moving forward while staying true to our history,
we're now the Road Free company.

camso.co



FORMERLY
CAMOPLAST
SOLIDEAL