

SOLIDEAL SOLIDAIR LT

BY CAMSO



RESILIENT



PNEUMATIC COMFORT WITHOUT COMPROMISE.

A solid tire with a unique aperture design prevents shock transfer to fragile or impact-sensitive loads. Provides operators with a more comfortable ride on uneven surfaces.

PERFORMANCE

ENERGY SAVINGS



TIRE LIFE



COMFORT



camsso.co



**ROAD
FREE
COMPANY**

FORMERLY
CAMOPLAST
SOLIDEAL

RESILIENT

SOLIDEAL SOLIDAIR LT

BY CAMSO

TIRE SIZE	RIM SIZE ⁽¹⁾	HEEL		ACTUAL TIRE DIMENSIONS		WEARABLE HEIGHT	LOAD CAPACITY ⁽²⁾ Counterbalanced lift trucks (kg)	
				OVERALL DIAMETER	OVERALL WIDTH		Load wheel	Steering wheel
		NORMAL	QUICK	(mm)	(mm)		Up to 25 km/h	Up to 25 km/h
5.00-8	3.00D-8	■	■	452	120	37	1415	1090
18 x 7-8 (180/70-8)	4.33R-8	■	■	453	154	38	2145	1650
6.00-9	4.00E-9	■	■	524	137	45	1885	1450
6.50-10	5.00F-10	■	■	570	158	51	2340	1800
23 x 9-10 (225/75-10)	6.50F-10	■	■	583	202	50	3445	2650
7.00-12	5.00S-12	■	■	652	165	54	2920	2240
27 x 10-12 (250/75-12)	8.00G-12	■	■	674	243	59	3900	3000
28x9-15 (8.15-15 & 225/75-15)	7.00-15	■	■	688	216	50	3770	2900
250-15 (250/70-15)	7.00-15	■	■	719	219	57	4750	3650
250-15 (250/70-15)	7.50-15		■	719	219	57	4750	3650
8.25-15 (7.50-15(32))	6.50-15	■	■	812	210	67	4750	3650
300-15 (315/70-15)	8.00-15	■	■	816	253	64	5850	4500

SOLIDAIR APERTURE DESIGN TECHNOLOGY

- Improves ride quality
- Great stability
- Low vibration and shock transfer



Remarks

(1) Check rim for size, especially on width, as this should correspond to tirebase marking. Check also max. load of rim with rim manufacturer, as wheel load will be restricted by lowest load capacity, either the one given by the rim or by the tire.

(2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted. Loads apply to cyclic service applications. Cyclic service means applications where there is a variation in load and/or speed. For further details, please consult the technical department. Loads are valid for intermittent service only. Intermittent service means a minimum load variation of 2.5. Does not include the additional weight of the solid tire when converting from pneumatics.

This document contains technical data of all products globally.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tire availability in your region.

AUTHORIZED DISTRIBUTOR: